

J.E. Patterson  
B.E., M.I.E.Aust., C.P.Eng

PO Box 622  
FYSHWICK ACT 2609  
89-91 Tennant Street  
FYSHWICK ACT 2609 Australia

Phone: 61 2 6241 2727  
Fax: 61 2 6241 1352  
E-mail: iic@iic.com.au  
Website: iic.com.au

### INSTALLATION OF AUSTRALIA POST TYPE 2 TIMELOCK CASH CONTAINERS

The Type 2 Timelock Cash Container is designed to fit into a recess in Australia Post's new standard counter. The container has a flanged base which is drilled for attachment to the panel on which it sits. There are four attachment points designed for ¼ inch coach bolts. The nuts are accessible with the door open, and the bolts should be cut so they do not protrude above the floor of the container.

#### ***Fitting the Battery***

- When the container is received the door will be locked and no battery installed.
- To connect the battery remove the battery cover on the right side of the lock case and pull out the battery connector.
- Connect the battery provided and leave hanging loose on the battery lead.
- Operate the lock as described on the following page, and open the door of the container.
- With the door open, insert the battery, terminals outermost, into the battery recess. Care should be taken to lay the connecting wires along the lower side of the battery. The extraction ribbon should be positioned so as to facilitate the removal of the battery.



**Operating the Lock**

- Key in the User Combination 111111. A red light will flash at intervals for the period of the preset three-minute time delay.
- At the end of the time delay, a green light will flash with an accompanying beep for the duration of the one-minute opening period.
- On completion of the time delay, and during the opening period, key in the User Combination again. A green light will flash for about 5 seconds during which the bolt may be retracted.
- Turn the dial clockwise to retract the bolt.
- Pull the door forward and down to open the container.

**NOTES****Spring Bolt Operation**

The dial will only turn in the first quadrant. After entering the correct combination after the time delay and retracting the bolt, the bolt will automatically return to its extended position when the dial is released. The Container will automatically lock whenever the door is closed.

**Wrong Try Penalty**

The lock will disable for a period of about three minutes after five incorrect combinations are entered. Thereafter, each incorrect combination will renew the lockout for a further three minutes. The lock will reset only when the correct combination is entered.

**Warranty**

The lock fitted to the container carries a two year replacement warranty. Should there be a problem with the lock during installation, contact International Industry Consultants Pty Ltd for advice. Do not attempt repair – there are no field repairable components inside the lock. **Cutting the yellow warning tape on the lock cover will void the warranty.**